

产品概览

AR0521: CMOS Image Sensor, 5.1 MP, 1/2.5"

欲看完整文档,请参阅数据表。

The AR0521 is a 1/2.5-inch CMOS digital image sensor with an active-pixel array of 2592 (H) x 1944 (V). It captures images in either linear or high dynamic range modes with a rolling-shutter readout, and includes sophisticated camera functions such as binning, windowing and both video and single frame modes. It is designed for both low light and high dynamic range performance, with line interleaved T1/T2 read out to support off chip HDR in an ISP chip. The AR0521 produces extraordinarily clear, sharp digital pictures, and its ability to capture both continuous video and single frames makes it the perfect choice for a security applications.

特性

- 5 Mp at 60 fps for Excellent Video Performance
- Small Optical Format (1/2.5-inch)
- 1440p Mode for 16:9 Video
- Superior Low-light Performance
- · 2.2 m Back Side Illuminated Pixel Technology
- · Supports Line Interleaved T1/T2 Readout to Enable HDR Processing in ISP Chip
- Support for External Mechanical Shutter
- · On-chip Phase-locked Loop (PLL) Oscillator
- · Integrated Color and Lens Shading Correction
- Slave Mode for Precise Frame-rate Control For more features, see the data sheet

应用

Video Surveillance

· High Dynamic Range Imaging

终端产品

- Security Camera
- Action camera
- Car DVR

器件电气规格											
产品	Compliance	Status	Туре	Megapixel s	Frame Rate (fps)	Optical Format	Shutter Type	Pixel Size (µm)	Output Interface	Color	Package Type
AR0521SR2C09SURA 0-DP	Pb-free Halide free	Active	CMOS	5.1	60	1/2.5 inch	Electronic Rolling and Global Reset Release	2.2 x 2.2	Multi	RGB	PLCC-52
AR0521SR2C09SURA 0-DP1	Pb-free Halide free	Active									PLCC-52
AR0521SR2C09SURA 0-DR	Pb-free Halide free	Active	CMOS	5.1	60	1/2.5 inch	Electronic Rolling and Global Reset Release	2.2 x 2.2	Multi	RGB	PLCC-52
AR0521SR2C09SURA 0-DR1	Pb-free Halide free	Active									PLCC-52
AR0521SR2M09SURA 0-DP	Pb-free Halide free	Active	CMOS	5.1	60	1/2.5 inch	Electronic Rolling and Global Reset Release	2.2 x 2.2	Multi	Mono	PLCC-52
AR0521SR2M09SURA 0-DR	Pb-free Halide free	Active	CMOS	5.1	60	1/2.5 inch	Electronic Rolling and Global Reset Release	2.2 x 2.2	Multi	Mono	PLCC-52

欲了解更多信息,请联系您当地的销售支援 www.onsemi.cn。

创建于:9/16/2018